



DAMPO

BIENVENIDOS
AL

TALLER DE ESTRUCTURAS
EQUIPADAS CON BRBs

EN UN MOMENTO INICIAMOS...





DAMPO

TALLER DE ESTRUCTURAS EQUIPADAS CON BRBs

Dr. Héctor Guerrero Bobadilla





DAMPO

**Engineering,
technology
& infrastructure.**



1. INTRODUCCIÓN



Conceptos básicos de los Contraventeos Restringidos al Pandeo





Conceptos básicos de los Contraventeos Restringidos al Pandeo





Conceptos básicos de los Contraventeos Restringidos al Pandeo






Conceptos básicos de los Contraventeos Restringidos al Pandeo





Conceptos básicos de los Contraventeos Restringidos al Pandeo

Buckling Restrained Braces (BRBs) Engineering Overview





Conceptos básicos de los Contraventeos Restringidos al Pandeo



Núcleo




Funda

Los CRPs son muy simples



Conceptos básicos de los Contraventeos Restringidos al Pandeo




1. El núcleo se coloca dentro de la funda y ésta se rellena de concreto.
2. Se coloca un material desmoldante para des-adherir el núcleo y la funda.



Conceptos básicos de los Contraventeos Restringidos al Pandeo



Comportamiento
histerético





Conceptos básicos de los Contraventeos Restringidos al Pandeo

BRBs como fusibles
estructurales





Conceptos básicos de los Contraventeos Restringidos al Pandeo

Experimentos




DAMPO



Conceptos básicos de los Contraventeos Restringidos al Pandeo

Experimentos





Conceptos básicos de los Contraventeos Restringidos al Pandeo

Experimentos





DAMPO



Conceptos básicos de los Contraventeos Restringidos al Pandeo

Experimentos





Conceptos básicos de los Contraventeos Restringidos al Pandeo

Experimentos





Conceptos básicos de los Contraventeos Restringidos al Pandeo

Experimentos




DAMPO



Conceptos básicos de los Contraventeos Restringidos al Pandeo



Experimentos





Conceptos básicos de los Contraventeos Restringidos al Pandeo


Experimentos





Conceptos básicos de los Contraventeos Restringidos al Pandeo



Experimentos





Conceptos básicos de los Contraventeos Restringidos al Pandeo

Experimentos







Conceptos básicos de los Contraventeos Restringidos al Pandeo






Conceptos básicos de los Contraventeos Restringidos al Pandeo





Conceptos básicos de los Contraventeos Restringidos al Pandeo

Experimentos



DAMPO



Conceptos básicos de los Contraventeos Restringidos al Pandeo

Soil Dynamics and Earthquake Engineering 31 (2011) 478–490

Estudios
numéricos



Contents lists available at ScienceDirect

Soil Dynamics and Earthquake Engineering

journal homepage: www.elsevier.com/locate/soildyn



Comparative seismic performance of steel frames retrofitted with buckling-restrained braces through the application of Force-Based and Displacement-Based approaches

Amador Terán-Gilmore^{a,*}, Jorge Ruiz-García^b

^a Universidad Autónoma Metropolitana, México

^b Universidad Michoacana de San Nicolás de Hidalgo, México

ARTICLE INFO

Article history:

Received 23 June 2010

Received in revised form

1 November 2010

Accepted 3 November 2010

ABSTRACT

This paper presents an analytical study aimed at evaluating the feasibility of using buckling-restrained braces as a retrofit scheme for existing multi-bay multi-story steel buildings. For that purpose, the seismic response of four two-dimensional frame models representative of typical steel buildings designed in a region of high seismicity was analyzed prior to and after including buckling-restrained braces as a retrofit strategy. The braces were designed following Force-Based and Displacement-Based approaches. The structural performance of the different versions of the frames was evaluated by subjecting each one to a set of twenty ground motions representative of the design earthquake with 10% exceedance probability in fifty years. It was observed that buckling-restrained braces allow for an efficient reduction in the peak drift demands in the retrofitted frames. However, since the beneficial effect of the braces cannot be fully controlled under a Force-Based design approach, it was concluded that a Displacement-Based design approach is the best option to achieve optimum structural performance.

© 2010 Elsevier Ltd. All rights reserved.

DAMPO



Conceptos básicos de los Contraventeos Restringidos al Pandeo

Estudios
numéricos

Conclusiones:

- Los métodos basados en desplazamientos son mejores porque permiten un mejor control de las distorsiones de entrepiso y del daño.
- CRPs permiten mitigar desplazamientos residuales.



Conceptos básicos de los Contraventeos Restringidos al Pandeo

Estudios
numéricos

THE STRUCTURAL DESIGN OF TALL AND SPECIAL BUILDINGS
Struct. Design Tall Spec. Build. (2011)
Published online in Wiley Online Library (wileyonlinelibrary.com). DOI: 10.1002/tal.716

Comparative reliability of two 24-story braced buildings: traditional versus innovative

Marco Montiel¹ and Amador Teran-Gilmore^{2,*†}

¹*Universidad Autonoma de Queretaro, Centro Universitario, Santiago de Queretaro, Queretaro, Mexico*

²*Materiales, Universidad Autonoma Metropolitana, Col. Reynosa Tamaulipas, DF Mexico*

SUMMARY

The seismic reliability of two 24-story buildings that have the same geometry and structural layout was evaluated and compared. The structural system of the first building consists of ductile steel braces and composite moment-resisting frames (traditional building). The structural system of the second building consists of nonductile flexible steel frames stiffened through a system of buckling-restrained braces (innovative building). Whereas the former was designed according to the Mexico City Building Code, the latter was designed according to a displacement-based methodology. Both buildings were assumed to be located at the same site in the lake zone of Mexico City. The study shows that in spite of being considerably lighter, the innovative building exhibits higher levels of reliability. Copyright © 2011 John Wiley & Sons, Ltd.

Received 9 August 2010; Revised 28 April 2011; Accepted 8 June 2011



Conceptos básicos de los Contraventeos Restringidos al Pandeo

Estudios
numéricos

Conclusiones:


La estructura equipada con CRPs :

- Redujo la cantidad de acero estructural a sólo el 40%.
- Presentó niveles de confiabilidad mayores.



Conceptos básicos de los Contraventeos Restringidos al Pandeo


Estudios
numéricos




Contents lists available at [ScienceDirect](#)

Engineering Structures

journal homepage: www.elsevier.com/locate/engstruct



Evaluation of the economic benefits of using Buckling-Restrained Braces in hospital structures located in very soft soils

 CrossMark

Héctor Guerrero^{a,*}, Amador Terán-Gilmore^b, Tianjian Ji^a, José A. Escobar^c



^a*School of Mechanical, Aerospace and Civil Engineering, The University of Manchester, Pariser Building, Manchester M13 9PL, UK*
^b*Universidad Autónoma Metropolitana, Department of Materials, México City, Mexico*
^c*Universidad Nacional Autónoma de México, Institute of Engineering, México City, Mexico*

ARTICLE INFO	ABSTRACT
<p><i>Article history:</i> Received 11 February 2016 Revised 16 January 2017 Accepted 17 January 2017</p> <p><i>Keywords:</i> Buckling-Restrained Braces (BRBs) Hospital structures Very soft soils Lakebed zone of Mexico City Economic benefits of BRBs</p>	<p>Since economic quantities are more meaningful to decision makers than dynamic response parameters, this paper examines the economic benefits of using Buckling-Restrained Braces (BRBs) in hospitals located in the very soft soils of the lakebed zone of Mexico City. Since non-structural elements and contents are far more expensive than the structure itself, they are included in detail in the analyses. The results of analyses on three-, six-, and nine-storey frames, which represent short-period structures, show that the expected (or probable) losses and lifecycle costs are smaller when structures are equipped with BRBs. Different cases (defined by the contribution of the BRBs to the strength capacity of the structure) were analysed and compared. The best design options were identified from a comparison of lifecycle costs. As an example, a comparison of cost-benefit analysis between a bare frame and a frame designed under gravity loads and equipped with BRBs, shows that the latter is more economical; because, for the same initial cost, the lifecycle costs are significantly smaller.</p> <p>© 2017 Elsevier Ltd. All rights reserved.</p>



Conceptos básicos de los Contraventeos Restringidos al Pandeo

Ventajas



Ahorro de acero estructural:
60%

(Teran y Montiel, 2011)



Conceptos básicos de los Contraventeos Restringidos al Pandeo

Aplicaciones



DAMPO



Conceptos básicos de los Contraventeos Restringidos al Pandeo

Reflexión:

- ¿qué esperamos?



DAMPO

Copilco 76 A9-304, Col. Copilco el
Bajo, Coyoacán, CDMX

www.dampo.com.mx

¡Gracias!

**Engineering,
technology
& infrastructure.**

ANTEPROYECTO

MODELACIÓN

DETALLADO

COSTOS

CONSTRUCCIÓN

REFUERZO

Asesoría especializada

En cualquier etapa del proyecto

Todo tipo de sistema de protección sísmica

- Predimensionamiento
- Guías y manuales de diseño
- Modelación y revisión
- Optimización y análisis de costos
- Visitas e inspecciones
- Ingeniería de detalle
- Estudios de riesgo

Venta de disipadores

Contraventeos Restringidos al Pandeo (CRP)

Otros sistemas

- Equipos de catalogo y fabricaciones especiales
- Patentes propias y fabricación nacional
- Estudios técnicos realizados en la UNAM

Visita:

www.dampo.com.mx

Contacto:

info@dampo.com.mx

5534116953



DAMPO

**Engineering,
technology
& infrastructure.**